THIS DRAWING AND SPECIFICATIONS, HEREIN, ARE THE PROPERTY OF DATA GENERAL CORPORATION AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN WHOLE OR IN PART AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION.

REVISIONS				
REV.	DESCRIPTION	DRFTG.	APP. BY	DATE
	ECO C40, Q65	RNK		10-13-70
	ECO 180, 217,	RNK		5-18-71

SEE BELOW FOR REV'S

REV	DESCRIPTION	DRFTG.	APP. BY	DATE
07	ECO # 1670	R.W.C.		6-22-72
06	NO CHANGE/ECO'S: 718 & 802	RNK		7-20-72
04	ECO 428	WJG		7-20-71
03	ECO 345	RNK		7-6-71
REV	DESCRIPTION	DRFTG.	APP BY	DATE

QTY.	DESCRIPTION	PART NO.

UNLESS OTHERWISE SPECIFIED— DIMENSIONS ARE IN INCHES
TOLERANCES ON FRACTIONS ± DECIMALS XX ± XXX ± ANGLES ±
PARTS TO BE FREE FROM BURRS BREAK ALL EDGES .010
UNLESS OTHERWISE SPECIFIED - ALL MACH. SURFACES

DRAWN
CHECKED
ENGINEER
APPROVED
FIRST USED ON 90190/9023/9029
MATERIAL
FINISH
SHEET OF

DATA GENERAL CORPORATION

TITLE: TELETYPE CONTROL

SIZE	CODE	DRAWING NUMBER	REV
D	001	000071	07

NOTE 1: REMOVE 470Ω 2W RES (R50) WHEN INSTALLING 4023 OPTION

NOTE 2: CHANGE 1MFD CAPACITOR (C39) TO .01 MFD WHEN 4023 OPTION INSTALLED

NOTE: CAPACITORS C16, C17, C18 C19, C21, C22, C23, C24 C32, C34, C35, C36, & C38 ARE .05 MFD. CAPACITORS C20, C25 & C40 ARE 6.8 MFD. THESE CAPACITORS ARE USED AS FILTERS AND AS SUCH ARE NOT SHOWN.

* CRYSTAL FREQUENCY OF Y2 DEPENDS ON BAUD RATE SPECIFIED BY THE CUSTOMER. (FREQ Y2 = 128 × BAUD RATE)

OPTION 4029

OPTION 4023 SEE NOTES 1 AND 2