THIS DRAWING AND SPECIFICATIONS, HEREIN, ARE THE PROPERTY OF DATA GENERAL CORPORATION AND SHALL NOT BE REPRODUCED OR COPIED OR USED IN WHOLE OR IN PART AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION

REVISIONS				
REV.	DESCRIPTION	DRFTG	APP. BY	DATE
	SEE BELOW FOR ECO # / REV			

REV	DESCRIPTION	DRAFT	APP BY	DATE
11	ECO 5479	M.C.		
10	ECO # 3855	TJK		5-7-76
09	ECO # 3569	ABS		4-16-76
08	ECO # 2460	A.M.C.		4-2-75

QTY.	DESCRIPTION	PART NO.

UNLESS OTHERWISE SPECIFIED— DIMENSIONS ARE IN INCHES
TOLERANCES ON FRACTIONS ± DECIMALS .XX ± .XXX ± ANGLES ±
PARTS TO BE FREE FROM BURRS BREAK ALL EDGES .010
UNLESS OTHERWISE SPECIFIED ALL MACH. SURFACES

DRAWN | CHECKED | ENGINEER | APPROVED | MATERIAL | FINISH

FIRST USED ON 4010/4023 4029

SHEET OF

DATA GENERAL CORPORATION

TITLE: TELETYPE CONTROL

SIZE D | CODE 001 | DRAWING NUMBER 000071 | REV 11

1 of 1

NOTE 1: REMOVE 470Ω 2W RES(R50) WHEN INSTALLING 4023 OPTION.
NOTE 2: REMOVE C39 (1MF) IF LINE IS 1200 BAUD RATE OR GREATER.
NOTE 3: REMOVE W7 (JUMPER). INSTALL W6 IF 4023 OPTION IS INSTALLED.
NOTE 4: FOR USE WITH MOD 37 TTY MOVE W9 JUMPER TO W8 POSITION

NOTE: CAPACITORS C6, C12, C18, C19, C21, C22, C23, C24, C32, C34, C35, C36, & C38 ARE .05 MFD. CAPACITORS. C20, C25 & C40 ARE 6.8 MFD. THESE CAPACITORS ARE USED AS FILTERS AND AS SUCH ARE NOT SHOWN.

* CRYSTAL FREQUENCY OF Y2 DEPENDS ON BAUD RATE SPECIFIED BY THE CUSTOMER. (FREQ Y2 = 128 × BAUD RATE)

OPTION 4029

OPTION 4023 SEE NOTES 1 AND 2